

Date: _____ PO#: _____
 Company: _____
 Contact: _____
 Phone: _____ Signature: _____

Ship To: _____

#	System Details			Color		Dimensions				Rail*		Sill+		Box	Location		Operator	Feed Exit	Feed Exit Override
	Shutter System	Vent** Y N		Curtain	Frame***	Width	FM+	Height	FM/RH	Size	S/R	L/U	Size	45°/90°	L	R			
1																			
2																			
3																			
4																			
5																			
6																			
7																			
8																			
9																			
10																			

+ SURCHARGE APPLIES

Gear and Override Options	#Ch
Removable Crank - 46"	
Fixed Crank - 46"	
Concealed/Special Crank - 53"	
Other	

Strap Options	#Wh	#Br
Recoil Box		
Strap Crank		

Wireless Controls	# White
Remote Transmitter 1 Channel	
Remote Transmitter 4 Channel +	
Wall Transmitter 1 Channel +	
Wall Transmitter 4 Channel +	
Key Pad +	

+ SURCHARGE APPLIES

Switch Controls	#Wh	#lv
Rocker Switch Maint.		
Rocker Switch Mom.		
Paddle Switch Maint.		
Paddle Switch Mom.		
Key Switch Mom. +		

+ SURCHARGE APPLIES

Left Side Right Side

Feed exit viewing direction as indicated.

Base Slat Lock:
- SURCHARGE APPLIES

- Slide
- Padeye
- Cylinder
- Commercial
 - Standard
 - Best

Lock Position

- (A) Back
- (B) Coil Side

Thumb Turn Position
[Commercial]

- (A) Back
- (B) Coil Side

*For rails: Standard is 12" with 1/2" holes. Comment if rails should be drilled otherwise.

** Light Slits are available for DuraComfort Line (A150, A200, A150H, A200H, A200HD), and SecuraMax RLL3

*** Frame consists of shutter housing, rails, and base slat.

Comments: _____

Notes: _____

